

UNDERLAY FOR TATAMIS

TJ13

Recommended on hard floor before installation of the tatami.
Polyurethane foam.
150kg/m³ in 2m00 x 1m00.
Thickness 30mm.
The unit.



Tatamis with Vinyl covering are M4 fireproof (According to FIRE AM6 and X16 of ERP requirements)

TATAMIS FRAME

Allows maintaining the Tatamis on the extremities
In polyurethane varnished fir wood.
With holes to fasten to the ground (without plugs neither bolts).
IMPORTANT : When placing the order specify **IMPERATIVELY** the outside dimensions of the tatami and if they are angles.
The linear meter.

TJ950	40mm thickness.
TJ960	50mm thickness.
TJ970	60mm thickness.
TJ980	70mm thickness.



WALL PROTECTION

- 22mm thickness - dimensions: 2m00 x 1m00 or TAILOR MADE the m².
- Polyethylene foam 30kg/m³.
- Covered by polyester coating.
- 2 classifications :
 - M2 for cover only.
 - M2 full (foam + cover).
- To install by double gluing Wall/protection by gel glue.

WALL PROTECTION - STANDARD

M2 fireproof cover. Without full fireproof classification.
6 colors possible.

TJ1310 Plaque of 2m00 x 1m00.

TJ1311 The M² (precise dimensions).

7 colors possible :



WALL PROTECTION M2 FULL FIREPROOF

M1 fireproof cover. With full fireproof M2 classification.
4 colors possible. HAVANA or GREY/BLUE.

TJ1315 Plaque of 2m00 x 1m00.

TJ1316 The M² (precise dimensions).

4 colors possible :



WALL PROTECTION M2 FULL FIREPROOF

TJ1315S

Same as TJ1315 and TJ1316 but with 5 specific colours to order.
Must be **IMPERATIVELY** ordered by multiples of 12 units.
Dimensions: 2m00 x 1m00
Set of 12 units.

5 colors possible :



GLUE

TJ1221

Gel glue for wall protections.
Tin of 5 litres for 4 protections.
The unit.

SPECIFIC PROTECTION ON STUDY